

# DIRECT HEAT SEALERS

## THS-200, THS-300, THS-400



Foot-operated direct heat sealers seal many types of thermoplastic packaging material. Depending on the model of the sealer, material up to 16" wide & 20 mil total thickness can be sealed. The meshed seal width is 15mm. The sealers are ideal for coated aluminum foil, Kraft paper, cellophane, polypropylene, poly-nylon, and other thick materials. The units are equipped with a thermostat that accurately controls the temperature from 30° to 550°F (0° to 300°C). Both jaws are heated simultaneously so there is a better heat penetration to seal thicker material. The sealers include an adjustable worktable. The pedestal stand is 26". An optional 36" stand is also available.

**Easy to operate:** Set the temperature on the thermostat for the material to be sealed. Once the correct setting has been reached, consistent seals will be maintained automatically. Insert the material between the two sealing bars. Press down on the footboard and release.

Size	Model#	Description	Watts	Wt.
8"	THS-200	8" Direct Heat Sealer	250w	54
12"	THS-300	12" Direct Heat Sealer	350w	59
12"	THS-300S	12" Direct Heat Sealer, Serrated	350w	59
12"	THS-3010S	12" Direct Heat Sealer, 10mm, Serrated	350w	59
16"	THS-400	16" Direct Heat Sealer	420w	62
16"	THS-400TC	16" Direct Heat Sealer, Teflon-coated	420w	62

- **STANDARD:** 15mm Meshed Seal (horizontal & vertical lines), 8", 12", & 16" (THS-200, THS-300, THS-400)  
*or with* Teflon-coated jaws, 16" (THS-400TC)
- 15mm Serrated Seal (horizontal line) 12" (THS-300S)
- 10mm Serrated Seal (horizontal line) 12" (THS-3010S)



meshed jaw



serrated jaw



### IT-863/RS-8

A 3-Line mountable imprinter is an available option. It mounts on the upper jaw of the sealer. Seal and print in one single operation. Ribbon colors available: black, blue, white, red, & gold.

THS-300IM 12" Direct Heat Sealer with Imprinter  
 THS-400IM 16" Direct Heat Sealer with Imprinter

MFG 02.12.09.  
 EXP 00.12.09.  
 LOT 735 B QD

**Printing Sample**  
 (actual size)